

### Product Data Sheet - Scaffold Access

## ALTO Cup System Scaffold Stair

ISSUE 02 DATE Jan 23

PAGE 1 of 2

### Overview

The Alto Cup System Scaffold Stair is an all-aluminium stair unit designed to be used on system scaffolding with 1.8m bays - typically Cuplok/Scaflok/Genlok/Tradlok. A cost-effective, safer alternative to using vertical ladders

Manufactured using structural grade aluminium for strength and reliability, the Alto Cup System Scaffold Stair is a simple and versatile solution for adding staircases to a Cup type system scaffold. Like all Alto products, the Alto Cup System Scaffold Stair is designed to be effective, durable and fully compliant with BS EN 12811.

There are three models in this range covering lift heights of 1.0, 1.5 and 2.0 metres.

## **Specification**

· · /	2	
WEIGHT	24.4 kg (2.0m version) 23.6 kg (1.5m version)	
	23.5 kg (1.0m version)	
OPERATING HEIGHTS	1.0m, 1.5m & 2.0m	
BAY SIZES	1.8m	
TREAD WIDTH	750mm	
OVERALL WIDTH	800mm	
KEY FEATURES	- Compatible with Cuplok/Scaflok/Genlok/Tradlok	
	system scaffolding	~
	- Durable, corrosion resistant construction	
	- Slip resistant stair treads	
	- Bolted construction for simple maintenance	m Version

- Bolted construction for simple maintenance





#### Lakeside Industries Ltd

Unit 19 Howard Road, Park Farm Industrial Estate, Redditch, Worcestershire. B98 7SE +44(0)1527 500577 | sales@altoaccess.com | www.altoaccess.com







Product Data Sheet - Scaffold Access

# ALTO Cup System Scaffold Stair

ISSUE 02 DATE Jan 23

23 PAGE 2 of 2

## Key Features

- Designed to give scaffolders a cost-effective stair access solution with practical, reliable & compliant equipment.
- The Alto Cup System Scaffold Stair gives a rapidly deployed solution for standard lift heights.
- Made to fit 1.8m bay scaffolding systems e.g. Cuplok/Scaflok/Genlok/Tradlok. With this product you can quickly install fully compliant stair access to your Cup system scaffold.
- The Alto Cup System Scaffold Stair can be installed without the use of any tools to lock the top hooks onto the transom.
- Three standard models in the range for the most common lift heights of 1.0m, 1.5m and 2.0m.
- Made with standardised components and an all-bolted construction, the Alto Cup System Scaffold Stair can be maintained by any competent operator.
- With a clear width of 750mm and slip-resistant extruded treads, the Alto Cup System Scaffold Stair is comfortable and convenient for the user.



#### Lakeside Industries Ltd

Unit 19 Howard Road, Park Farm Industrial Estate, Redditch, Worcestershire. B98 7SE +44(0)1527 500577 | sales@altoaccess.com | www.altoaccess.com



